



Industrial Range

MODEL 556



- ▶ Ranges from 1 to 70 bar
- ▶ Standard Accuracy to 0.02%

Pneumatic Dead-Weight Testers.

Primary standards for Pressure Calibration

- ▶ Class 'A' Accuracy to 0.0065%
- ▶ Supplied with Software



DH-Budenberg The Pressure Reference

Industrial Range

MODEL 556

Pneumatic Dead-Weight Testers.

Primary standards for Pressure Calibration

Standard Accuracy to 0.02%
Class A with UKAS
Calibration Certificate 0.0065%

RANGES:

Bar 1 to 70
kPa 100 to 7000
lb/in² 15 to 1000



ACCURACY

All certificates issued for DH-Budenberg Dead-weight Testers are fully traceable to national standards via equipment with UKAS calibration certificates. A standard accuracy of 0.02% is achieved from 10% of range using software supplied to compensate for the effects of gravity, temperature and the actual area of piston unit. Standard accuracy without any corrections for actual area is 0.03% from 1 to 70 bar. Higher accuracy Class A testers are available (supplied with UKAS Calibration certificates for area and mass) allowing an accuracy of 0.0065% to be achieved.

WEIGHTS SUPPLIED

+ includes making-up weight or screw

1 to 70 bar	100 to 7000 kPa	15 to 1000 lb/in ²
Piston+ 1	Piston+ 100	Piston+ 15
1 wt 9	1 wt 900	1 wt 185
5 wts 10	5 wts 1000	3 wts 200
1 wt 5	1 wt 500	1 wt 100
2 wts 2	2 wts 200	1 wt 50
1 wt 1	1 wt 100	2 wts 20
1 wt 0.5	1 wt 50	1 wt 10
2 wts 0.2	2 wts 20	1 wt 5
1 wt 0.1	1 wt 10	2 wt 2
1 wt 0.05	1 wt 5	1 wt 1
		1 wt 0.5

Owing to limited demand weights marked in kg/cm² are not stocked.

The 550 base can be used with any 550 series pistons, allowing testing from 15 mbar to 120 bar. The base requires a supply of Gas slightly above the test pressure, and has precision inlet/outlet valves and a screwpress to enable easy regulation and adjustment of pressure.

The 556 has a 1/16in² piston/cylinder unit operating to 70 bar and works on pure gas. The design uses a re-entrant type cylinder, high chrome steel piston to achieve excellent performance across the entire operating range.

SOFTWARE

For maximum ease of use, computer software is supplied with all units. There are two software packages, one for standard accuracy, one for Class A. The software allows the users to correct for the effects of environmental factors such as gravity and temperature and to determine the precise pressure generated by the Dead-weight testers.

ACCESSORIES

There are many accessories which can be supplied for use with the Dead-weight testers. These include liquid / liquid seals, two gauge stands and many others. DH-Budenberg have extensive experience in the use of Dead-weight testers and can supply accessories for many applications. A separate data sheet of accessories is available.

PACKING DETAILS

1 carton containing base, tool roll and piston unit:
59 x 49 x 38cm. 0.110m³, Nett 18kg, Gross 21kg.
1 carton containing weights:
32 x 32 x 38cm. 0.04m³, Nett 29kg, Gross 32kg.

SPARES, REPAIR AND RE-CERTIFICATION

Comprehensive service and calibration capability of both DH-Budenberg and non DH-Budenberg test equipment: Dead-weight Testers (working service or full overhaul).

Portable calibrators (DH-Budenberg & non- DH-Budenberg).

Comparators.

All accuracy ranges can be supplied with UKAS Calibration Certificates.

Certification traceable to national standards.

Rapid turn-around times and hire items available as a temporary replacement for strategically important plant.

For further information on Accessories, Repairs & Recertification contact DH-Budenberg and ask for a Data sheet.



Calibration Dynamics Ltd
7 Regents Court
South Way
Walworth Industrial Estate
Andover
Hampshire SP10 5NX

TELEPHONE
+44 (0) 1264 339030
FAX
+44 (0) 1264 339040

WEBSITE
<http://www.calibrationdynamics.com>
EMAIL
sales@calibrationdynamics.com